

The AQUA-TANK can be folded up and neatly stored away during the off season and brought out again when your garden needs it the most.

CONTENTS

Each AQUA-TANK includes everything you need to get started:

- > 1 x UV resistant PVC tank
- support legs 50L x 4; 100L x 5; 225L and 400L x 6; 750L x 9 and 1,000L x 11
- > 1 x tap and 2 washers which connects to a standard garden hose
- > 1 x filter in the lid to remove any leaves or debris (available only for the 100L, 225L, 400L, 750L and 1.000L)
- > 1 x overflow valve and 2 washers (available only for the 100L, 225L, 400L, 750L and 1,000L)

PREPARATION

- Please read and understand these instructions before assembling your AQUA-TANK.
- > Check that you have all the components.
- > Choose a flat area near your downpipe for the location of your AQUA-TANK.



50 LITRE TANK

350mm diameter x 530mm high Box Size/Weight: 520 x 160 x 130mm/1.35kg



100 LITRE TANK

430mm diameter x 750mm high Box Size/Weight: 735 x 180 x 125mm/1.8kg



225 LITRE TANK

635mm diameter x 810mm high Box Size/Weight: 785 x 180 x 125mm/2.7kg



400 LITRE TANK

680mm diameter ×1,110mm high Box Size/Weight: 1,120 x 185 x 125mm/4.8kg



750 LITRE TANK

900mm diameter x 1,170mm high Box Size/Weight: 1,190 x 180 x 140mm/6.25kg



1,000 LITRE TANK

1,200mm diameter × 900mm high Box Size/Weight: 900 × 210 × 170mm/6.9kg

ASSEMBLY INSTRUCTIONS

Also watch our instructional animation on our website www.aqua-tank.com.au

Unfold your AQUA-TANK and screw the tap into the fitting at the bottom on the outside of the tank. Ensure you fit a rubber washer over the threaded section before fitting it to the tank and also place a rubber washer on the inside before screwing the round retaining nut into position.



2 From the outside of the tank, screw the overflow valve into the fitting at the top side of the tank making sure you have placed one washer on the inside of the tank and also on the outside of the tank to ensure a firm fit.



3 Screw the filter into the underside of the tank lid.



4 Lay your AQUA-TANK on its side and insert the support legs into the sleeves (1 per sleeve) on the side of the tank. Please note there are 4 legs for the 50L, 5 for the 100L, 6 for the 225L and 400L, 9 for the 750L and 11 for the 1,000L.



5 Stand the tank upright and zip up the lid all around ensuring that it is completely closed.



USE

- 1) Position your AQUA-TANK near a downpipe on a firm flat surface.
- 2) Position the end of the downpipe to the filtered opening on the lid of the tank. It may be necessary to cut the downpipe and/or add an elbow joint. Alternatively, unzip a portion of the lid and insert the downpipe into the tank, but this will not allow for any filtering.
- Add about 50mm of water to the tank to give it stability while waiting for rainfall
- 4) Once water is collected in your AQUA-TANK, water can be emptied through the spout using a standard garden hose, or unzip the lid and dip a watering can or similar to water your plants.
- 5) Periodically check the filter to remove any debris.
- 6) The overflow valve can be kept closed or opened as needed.
- 7) You may connect a hose to the overflow valve to divert water to a preferred location or to multiple tanks.
- 8) If you live in an area where you may experience freezing conditions during the winter months, ideally you should empty your tank and store in a mild environment

CAUTION

- > Never allow children to play in or around your AQUA-TANK.
- > Always securely close the lid to prevent access when not being used.
- Never drink water from your tank. Use the AQUA-TANK water only for watering plants or other outdoor purposes.
- > Always place your tank on a firm, level horizontal surface.
- > When using tools for installing drain pipes use safety glasses and protective gloves.

E. info@aqua-tank.com.au

W. aqua-tank.com.au





AQUA-TANK is the registered trademark of Hy-Grow Systems Pty. Ltd.